

## G-MOUNT HF (M5)

### Mobile mount for roof mounting

Mobile mount for roof mounting of antenna whips supplied with external M5 threaded stud. It can be mounted from the inside or from the outside.

- LOW PROFILE DESIGN
- TILTABLE IN ALL DIRECTIONS



#### Electrical Specifications:

Frequency	0 - 2500 MHz (External antenna whips)
-----------	---------------------------------------

Impedance	50 ohm
-----------	--------

#### Mechanical Specifications:

Color	Black
-------	-------

Diameter	33 mm
----------	-------

Mounting	Bolt-on. Mounting from inside: Ø 13 mm, Mounting from outside: Ø 19 mm
----------	--

Materials	ABS, POM, PE, brass and steel
-----------	-------------------------------

Operating temperature	-40C to +70C
-----------------------	--------------

Connector 1	See "ORDERING INFO" (Other types available)
-------------	---

Cable	See "ORDERING INFO" (Other lengths available)
-------	---

Mounting place	On vehicle roof
----------------	-----------------

Mounting Instruction	External antenna is tiltable 30° in all directions by bending the topsection of the base. NOTE! Bending one time only ! Maximum torque is 4.5Nm.
----------------------	--

Height above roof	30 mm
-------------------	-------

Mounting hole	13 mm
---------------	-------

Build-in depth	Approx. 12 mm
----------------	---------------

Ingress Protection	IP65 (When mounted)
--------------------	---------------------



---

**Ordering information:**

Part no.	G16060 (0.15 m cable + FME-male)
Part no.	G16060IP (0.15 m cable + FME-male - Bulk packing)
Part no.	G16062 (0.15 m cable + SMA-female)
Part no.	G16062IP (0.15 m cable + SMA-female - Bulk packing)
Part no.	G16064IP (5 m cable + SMA-male - Bulk packing)
Part no.	G16065IP (5 m cable + open end - Bulk packing)

---



---

**Packing information:**

Packing	Polybag or bulk
---------	-----------------

---



G-Mount Instruction

# MOUNTING INSTRUCTION

