

# CMA35/a 0 dB

## End-fed full $1/2 \lambda$ coaxial dipole antenna

- Full omni-directional radiation pattern
- DC-grounded (DC-short) - antistatic
- NO GROUNDPLANE NEEDED

Electrical Specifications:

Frequency	380 - 400 MHz (TETRA)
Impedance	50 ohm
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Bandwidth	20 MHz
VSWR	< 1.5
Max. Power	250 W

Mechanical Specifications:

Color	White
Height	Approx. 1130 mm
Weight	400 g
Mounting	On 1" threaded pole (G1"-11 thread) with Revolving Nut Kit or on optionally brackets
Materials	PU-painted heavy-duty $\varnothing$ 18 mm glass-fibre tube and chrome plated brass
Operating temperature	-40C to +70C
Connector 1	N-female
Cable	No cable supplied
Mounting place	On mast etc.
Ingress Protection	IP66
Serial no.	On product label

Ordering information:

Part no.	12390 (Antenna whip only)
Part no.	12390IP (Antenna whip only - Bulk Packing)
Part no.	13391 (Revolving Nut Kit 15027 included)



Datasheet 2 / 2

Packing information:

Packing	Polybag or bulk
---------	-----------------

