

# CHP HS

## SINGLE EAR-CUP FOR HARD HAT MOUNTING



The CHP HS is available in single (HS) and double (HD) ear-cup variants. Both incorporate high impact polymer ear-cups with a noise-cancelling boom microphone. Universal hard hat adaptors are provided, however a range of specific adaptors are available upon request.

The large diameter earpiece speakers and noise-cancelling boom microphone combine to ensure loud & clear audio in both directions. The headset provides both voice operated transmit (VOX) and push-to-talk (PTT) functionality.

Included with the headset is Entel's large, quick release, PTT switch. This switch allows the radio to be operated easily, even with gloved hand operation or under clothing. All Entel accessories are secured to the radio via a heavy duty down-lead and with locking accessory connector.

### Features:

- ✔ Single ear-cup each with soft gel cups
- ✔ Also available as double cup version
- ✔ Hard-Hat / Helmet mountable
- ✔ Noise-cancelling Microphone
- ✔ IP54 Robust Construction
- ✔ Supplied with large, quick release IP68 Submersible PTT switch
- ✔ ATEX & IECEx Approved variants available



### Attenuation according to EN 352/ISO 4869

Mean: Mean value in dB — SD: Standard deviation in dB — APV: Assumed protection in dB

Frequency in Hz	63	125	250	500	1000	2000	4000	8000	SNR	H	M	L
Mean	15.4	22.8	27.4	31.3	30.5	28.2	35	34.6				
SD	3.5	4.3	3.2	2.8	1.8	2.3	3.6	3	30	28	28	24
APV	11.9	18.5	24.2	28.5	28.7	25.9	31.4	31.6				

Part #	Hards hat manufacturer
3711 - 1000242	Centurion
3712 - 1000243	Balance, Bullard, Centurion, JSP, LAS, MSA, Peltor, Voss, Opus
3714 - 1000245	Protector, AO, JSP, Domeguard
3717 - 1000248	JSP
3718 - 1000249	AO Safety, Bullard, Jackson, NSA, North, Honeywell
3721 - 1005292	Protector, Sofop, Petzel

Spare Parts	Part Number
Hygiene Kit	HY9
PTT Switch	PTT450E, PTT750E, PTT950E

## Contact

For more information about our products please contact us:

☎ **+44 (0)20 8236 0032**    ✉ **info@entel.co.uk**    💻 **entel.co.uk**

All Rights Reserved. Copyright Entel UK Ltd.

