
FST-GP2009W Alphanumeric Pager



- ★ Hand and PC programmable. USB id programmer.
- ★ PLL or crystal, 137-930Mhz, POCSAG or Flex
- ★ Alert mode: Sound, vibrate, LED, Silent.
- ★ 4 or 8 line English display, 3 zoom mode (English). Single color or double color.
- ★ Language support: Chinese, English, Germany, Korean, Turkey, Farsi, French, etc.
- ★ Out of range, low battery, repeat message, unread message indicator.
- ★ Menu selectable, User choice special functions for themselves.

- ★ Second watch function
- ★ Rechargeable Li battery



Specification (POCSAG)

Frequency Range: 138-930 MHz

Cap Codes: 8

Receiver Type: Synthesized or Crystal

Baud Rate: 512, 1200, 2400 bps

Paging Sensitivity: -106DB @ 512 bps

-105DB @ 1200 bps

-104DB @ 2400 bps

Channel Spacing: 25 KHz or 12.5 KHz

Frequency Deviation: +/-4.5 KHz

Frequency Stability: +/- 10PPM

Selectivity: > 55dB

Image Rejection: > 52dB

Spurious Rejection: > 55dB

Intermediation: > 50dB

Alert Tone Loudness: 72dB+ @ 12 inch

Display: 16 characters / line, 22 characters max

Memory Capacity: up to 3000 characters

Messages: 19 max

Weight: 60 g with battery

transVoice

Dimensions: 46*46*14 mm

Battery Type: Li battery

Operating Temperature: -10o to 50o C