

### FEATURES

- High Resolution 5" Digital TFT LCD
- Free Input voltage (DC 10V ~ 30V)
- LED Backlight technology (250cd/m2)
- Capacitive Touch Key
- Shutter camera support
- 2 Camera Inputs
- 2 Trigger Inputs
- Tamperproof function
- Anti Reflection Window
- Automatic Brightness Control
- Auto Scan function
- Auto Power ON/OFF
- NTSC/PAL Auto Switch
- Multi-lingual OSD control
- Built-in Speaker
- Electronic Distance Marker (Parking line)
- Bracket rails and Heavy Duty mounting possibility
- Speedswitch function via tacho signal (in case of frontview purpose)
- Sunvisor – included



### Specifications

|                              |  |
|------------------------------|--|
| <b>Power input</b>           | <b>10V~30V DC</b>  |
| <b>Video System</b>          | <b>NTSC, PAL signal Compatible</b>   |
| <b>Panel</b>                 | <b>5" Digital</b>  |
| <b>Resolution</b>            | <b>640(H) X 480(V) X RGB</b>   |
| <b>Format</b>                | <b>4:3</b>   |
| <b>Brightness</b>            | <b>250cd/m2</b>  |
| <b>Contrast Ratio</b>        | <b>500:1</b>   |
| <b>Display Mode</b>          | <b>Single</b>  |
| <b>Speaker</b>               | <b>8 ohm/0.3Watt</b>   |
| <b>Viewing Angle</b>         | <b>Top: 50°, Bottom: 70°, Left: 70°, Right: 70°</b>                                  |
| <b>Operating Temperature</b> | <b>-35°C ~ 80°C</b>  |
| <b>Dimensions</b>            | <b>148(W) X 104(D) X 29(H)mm</b>   |
| <b>Weight</b>                | <b>Approx. 500g</b>  |
| <b>Accessories</b>           | <b>- Bracket (Rail Type)<br/>- Screw kit<br/>- Sunvisor<br/>- Instruction manual</b> |