

Display

21.5" LED Backlight Monitor HS-ML22W4 /Wide Viewing Angle



- Professional LED Backlight Monitor for surveillance.
- Compatible with VGA(640 x 480), SVGA(800 x 600), XGA(1024 x 768), SXGA(1280 x 1024), Full HD (1920 x 1080) resolution.
- All plastic case.
- Video input HDMI x 1 / BNC x 1 / VGA x 1.
- Video output BNC x 1.
- Audio input RCA x 2 / phone jack x 1.
- Audio speaker x 2.
- Support multimedia USB x 1.
- Support HDMI 1080p.
- Excellent HD image and super wide viewing angle
- Built-in 3D comb filter and 3D de-interlace for crispy picture performance.
- Fast response time and refresh rate without time lagging.
- Provides 6500°K and 9300°K color temperature selection for user's preference.
- Video Inputs support NTSC / PAL standards.
- Video looping Output supports 75ohm auto termination.
- VESA standards (100mm x 100mm) bracket.

Specifications

Model	HS-ML22W4	Wide Viewing Angle(optional)
Button Control	Power / OSD Control / Source	
Display Resolution	640 x 480 @ 60/72/75 800 x 600 @ 56/60/72/75 1024 x 768 @ 60/70/75 1280 x 1024 @ 60/75 1280 x 720 @ 60 1360X768 @ 60 1440 x 900 @ 60 1680X1050 @ 60 1920 x 1080 @ 60	
Video Timing(HDMI)	480i / 480p / 576i / 576p / 720p / 1080i / 1080p	
Active Area	476.64(H) x 268.11(V)mm	
LCD Panel Type	TN mode, Normally white	
Dot Pitch	0.248(H) x 0.248(V)mm	
Display Ratio	16:9	
Display Color	16.7M colors	
Brightness (Central)	400 cd/m ²	250 cd/m ²
Contrast Ratio	1000 :1	3000 :1
Viewing Angle	Left 85° / Right 85° / Up 80° / Down 80° CR>10	Left 89° / Right 89° / Up 89° / Down 89° CR>10
Response Time	5 ms	30 ms
Input Voltage	DC12V	
Input Signal	1Vp-p composite video	
Input Impedance	75 ohm	
Output Signal	1.0Vp-p±0.2Vp-p composite video (75 ohm Auto Termination)	
Scanning system	NTSC:525 lines, 60 fields / sec ; PAL:625 lines, 50 fields / sec	
Video Input / Output	HDMI x 1, Video In x 1(BNC), Video Out x 1(BNC), VGA x 1	
Audio Input	Audio In x 2, PC-Audio In x 1	
Multimedia	USB x 1 (JPEG, MPEG4)	
Speaker	1W + 1W	
Power Consumption	20W	
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)	
Storage Temperature	-10°C ~ 60°C (14°F ~ 140°F)	
Dimension	516(W) x 411.4(H) x 55(D)mm	
Weight	N.W./G.W.: 3.6KG / 5.3KG	

Dimension Unit : mm

