152-951 Undervannskamera m/ 6-22mm zoom objektiv 100m kabel



Features:

- @ SONY 2MP COMS Sensor
- @ High Sensitivity; High Performance (Star Lighting Class)@ Enhanced
- OSD Function to adjust the image
- @ Advance design with decompression compartment for suitable operation under water@ Use Anode processed Surface
- @ Under Water down to 70 Meters
- @ 48 White LED Illumination Range: Up to 20 Meters
- @ UTC controller for switching LED lamp to ON/OFF, OSD and Zoom / Focus

Specifications:

Model No.	FST-W7020M3-100
Effective Pixels	1920 * 1080 Approx. 2M Pixels
Scanning System	Progressive
Syne System	Internal Syne
Video Output	1Vpp Composite Output, 75 ohms AHD or TVI
Lens	6-22mm Motorized Zoom Lens
Resolution	1920 * 1080P
Gamma Correction	0.45
Minimum Illumination	0.01 Lux
S/N Ratio	65 dB {AGC Off)
Power Source	DC12V
Power Consumption	5W (at LED ON and Zoom)
Ambient	-10-50°C/30-90% RH
Dimensions	134(0) x73(<l>)mm</l>
Weight	Approx. 2,000g (Excluding cable)
Backlight compensation	Default OFF (AREA adjustable)
White Balance	ATW (Default)/AWB/AWC->SET/Manual/Indoor
Gain control	Setting through UTC/OSD menu 0-15
Image correction	Image Reverse (mirror); Sense up; Slow Shutter
Motion Detection	4 AREA adjustable
OSD Language	English/Russian/German/Chinese/Polish/Turkish/
	Portuguese/Italian
Picture sharpness	0-10 Adj. (OSD setting)

www.holund.no