

NG-MOUNT (FME)

Mobile coaxial roof mount for non-conductive surface mounting

Mobile roof mount with integrated coaxial FME-male connector for non-conductive surface mounting of $1/2 \lambda$ portable antenna whips with FME-female connector.

NOTE: Not suitable for $1/4 \lambda$ antenna whips unless sufficient groundplane is being provided !

- NON-CONDUCTIVE SURFACE MOUNTING
- COAXIAL FME CONNECTION TO ANTENNA WHIP



Electrical Specifications:	
Frequency	0 - 2500 MHz
Impedance	50 ohm
Mechanical Specifications:	
Color	Black
Diameter	33 mm
Mounting	Bolt-on (From inside or outside)
Materials	ABS, POM, PE, brass and steel
Operating temperature	-40C to +70C
Connector 1	See "ORDERING INFO" (Other types available)
Cable	See "ORDERING INFO" (Other lengths available)
Mounting place	On non-conductive vehicle roof etc.
Height above roof	30 mm
Mounting hole	Mounting from inside: Ø 13 mm, Mounting from outside: Ø 19 mm
Build-in depth	Approx. 12 mm
Ingress Protection	IP65 (When mounted)



Ordering information:

Part no.	16090 (3 m cable + FME-female)
Part no.	16090IP (3 m cable + FME-female - Bulk packing)
Part no.	16104 (4 m cable + FME-female)
Part no.	16104IP (4 m cable + FME-female - Bulk packing)
Part no.	16105 (0.1 m cable + FME-male)
Part no.	16105IP (0.1 m cable + FME-male - Bulk packing)
Part no.	16136 (5 m cable + FME-female)
Part no.	16136IP (5 m cable + FME-female - Bulk packing)
Part no.	16137 (1.5 m cable + FME-female)
Part no.	16137IP (1.5 m cable + FME-female - Bulk packing)
Part no.	16111IP (10 m cable + SMA-male - Bulk packing)
Part no.	16192IP (3 m cable + SMA-male - Bulk packing)
Part no.	16195IP (1.5 m cable + SMA-male - Bulk packing)
Part no.	16408IP (10 m cable + FME-female - Bulk packing)

Packing information:

Packing	Polybag or bulk
---------	-----------------



