



Flexible Whip


- Flexible whip
- Removable for car wash
- UHF frequency

This antenna features a flexible construction within a black nylon tube. The design provides damage resistance without compromising RF performance.

The Panorama mounting system provides a high degree of interchangeability between whips and bases, making them suitable for all applications whether temporary or permanent.

The AFB range is suitable for use with all Panorama GPS combination and light duty magnetic bases.


Technical Drawing




Panorama Antennas Ltd



Product Data



* VSWR shown is AFB-S1 on a 1x1m (3'x3') ground plane with 5m of CS23 (RG58 c/u) cable



Part No.	111			14 TO 15 15	THE RESERVED		
		AFB-S1	AFB-S2	AFB-TET	AFB-UT	AFB-S4	
Electrical Dat	ta						
Frequency Range (MHz)		380-400	310-430	380-430	406-472	450-470	
Gain: Isotropic				2dBi			
Compared to 1	/4 wave			0dB			
Polarisation		Vertical					
Pattern			Omni-directional				
Impedance		50Ω					
Max Input Power (W)		100					
Mechanical D)ata					T JI SA	
Dimensions (mm)	Height	158 (6.2")	148 (5.8")	154 (6.1")	140 (5.5")	130 (5.1")	
	Diameter	10(0.4")					
Operating Temp (°C)		-40° / +80°C (-40° / 176°F)					
Material			Stranded speedo cable & Nylon•				
Colour			Black				
Mounting Da	ta					32500	
Fixing			M6 x 0.75 (GPSB, GPSK & MAR bases)				