

Datasheet 1/2

G135-300 0 dB RIGID (M5)

Rigid full 1/4 λ customer tunable antenna whip

Rigid customer tunable antenna whip especially made for use with "G"-type mounts (bases) on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- CUTTING TABLE FOR TUNING SUPPLIED

Electrical Specifications:		
Frequency	135 - 300 MHz (2M-BAND)	
Impedance	50 ohm	
Polarisation	Vertical	
Gain	0 dBd, 2.1 dBi	
Bandwidth	15 MHz	
VSWR	< 2.0	
Max. Power	200 W	

Mechanical	Specifications:
------------	-----------------

Color	Black		
Height	Approx. 510 mm (Before cutting)		
Weight	30 g		
Mounting	On "G"-type mounts		
Materials	Stainless steel, PE and brass		
Operating temperature	-40C to +70C	•	
Connector 1	M5 threaded stud		
Mounting place	Vehicle roof		
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included		
Ordering information:			
Part no.	G12050		

G12050IP (Bulk packing)

Polybag or bulk



Part no.

Packing

Packing information:



Datasheet 2 / 2



