

Datasheet 1/2

# E135-300 0 dB RIGID (M6)

## Rigid full 1/4 $\lambda$ customer tunable antenna whip

Flexible customer tunable antenna whip especially made for use with "E"-type mounts (bases) on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- **CUTTING TABLE** FOR TUNING SUPPLIED

Electrical Specifications:		
Frequency	135 - 300 MHz (2M-BAND)	
Impedance	50 ohm	
Polarisation	Vertical	
Gain	0 dBd, 2.1 dBi	
Bandwidth	20 MHz	
VSWR	< 2.0	
Max. Power	100 W	

### **Mechanical Specifications:**

Color	Black
Height	Approx. 515 mm (Before cutting)
Weight	28 g
Mounting	On "E"-type mounts
Materials	Stainless steel, PE and brass
Operating temperature	-40C to +70C
Connector 1	M6 Internal thread
Mounting place	Vehicle roof
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Ordering information	

#### Ordering information:

Part no.	E12044	
Part no.	E12044IP (Bulk packing)	

#### Packing information:

		V 0 - 0 -
Packing	Polybag or bulk	





Datasheet 2/2



