

Name	TP-Link Archer MR200
Code	N3262
Standards	IEEE 802.11ac/n/a 2.4 & 5 GHz
Transmission speed (WiFi) 802.11	5 GHz: up to 433 Mb/s 2.4GHz: up to 300 Mb/s
Operating bands [GHz]	2.4 5
Max output power [dBm]	20
Modulation	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Sensitivity	5GHz: 11a 54Mb/s: -74dBm 11ac HT20: -67dBm 11ac HT40: -64dBm 11ac HT80: -60dBm 2.4GHz 11g 54M: -76dBm 11n HT20: -73dBm 11n HT40: -67dBm
LTE/3G	4G: FDD-LTE B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz) TDD-LTE B38/B39/B40/B41 (2600/1900/2300/2500MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 (2100/900MHz) 4G: FDD-LTE Cat4 (800/900/1800/2100/2600MHz) TDD-LTE (2300/2600MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS (900/2100MHz) 2G: EDGE/GPRS/GSM (850/900/1800/1900MHz)
Interfaces	4x10/100 Mb/s LAN (1 port LAN/WAN)
Advanced functions	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Antennas	2x integrated (LTE) 3x internal (WiFi)
Power	100-240 VAC / 12 VDC
Operating temperature range [°C]	0...40
Operating humidity (RH)	95% (no condensation)
Dimensions [mm]	202x141x33