


- Fixed output voltages
- Short circuit proof
- Exchangeable DC plugs
- Faste utgangsspenninger
- Kortslutningssikker
- Utskiftbare DC plugger



Technical specifications	Tekniske data	12 V*
Input voltage:	Inngangsspenning:	190-264 VAC
Output voltage:	Utgangsspenning:	12,0 ± 0,5 VDC
Output power:	Utgangseffekt:	14,5 W
Max. load current:	Maks. laststrøm:	1,1 A
Load regulation:	Lastregulering:	< 1,0%
Line regulation:	Linjeregulering:	< 0,1%
Switch frequency (self oscillating):	Svitsjefrekvens (selvsvingende):	20-90 kHz
Temperature range:	Temperaturområde:	-10°C - +50°C
Ripple:	Rippel:	< 100 mV p-p
Efficiency:	Virkningsgrad:	> 80%
Current limiting:	Strømbegrensning:	1,2 A ± 0,1 A
Overvoltage protection:	Overspenningsbeskyttelse:	zener
Insulation class:	Isolasjonsklasse:	II
Electrical safety standard:	Elektrisk sikkerhetsstandard:	EN 50083-1, EN 60065, EN 60950
EMC standards	EMC standarder	
• Emmision:	• Emisjon:	EN 61000-6-3
• Immunity:	• Immunitet:	EN 61000-6-1
Output terminals	Utgangsterminaler	
• Cord with/without plug:	• Sek. ledning med/uten plugg:	Accessories / Tilbehør
Dimensions without plug (LxWxH):	Mål uten plugg (LxBxH):	75x48x33 mm
Weight:	Vekt:	100 g

* Some technical specifications may differ for other voltage versions. / Visse tekniske data kan variere for de forskjellige spenningsversjoner.

Voltage versions 9722 - Spenningsversjoner 9722

Input (VAC) Inngang (VAC)	Output (VDC) Utgang (VDC)	Max. load (A) Maks. last (A)	Output power (W) Utgangseffekt (W)
	Nom. / Nom.		
230	7,5	1,45	11,0
230	9,0	1,4	13,5
230	12,0	1,1	14,5
230	15,0	1,0	15,0
230	18,0	0,7	14,5
230	24,2	0,6	14,5