

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_UHF-0-3-3/033\_

Rev.: F



### Description

Straight cable jack

Interface Standards  
IEC 60169-12

### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 0.2 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0301 kg

#### Environmental Data

Operating Temperature -55 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Crimp ferrule	Copper

##### Surface Plating

Silver Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing	DOU-00181692
Catalogue drawing	DCA-00005871
Assembly instruction	DOC-0000201061

#### Ordering Information

Single package	21_UHF-0-3-3/033_E
----------------	--------------------

#### Additional Information

Suitable cables	RG_58_C/U, G_03232, GX_03272
-----------------	------------------------------



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Technology**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**