

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_UHF-0-7-4/033\_



### Description

Straight cable jack

Interface Standards  
IEC 60169-12



### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 0.2 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0324 kg

#### Environmental Data

Operating Temperature -55 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00007985  
Catalogue drawing DCA-00006309  
Assembly instruction DOC-0000201061

#### Ordering Information

Single package 21\_UHF-0-7-4/033\_E

#### Additional Information

Suitable cables RG\_213\_U, GX\_07272, G\_07262, G 07272

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!  
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**